

305 4-Way Fogger

MODEL # 950104

OVERVIEW

The 305 4-Way Fogger is a damp mist sprayer that uses compressed air (up to 29.5 CFM / 50.1 Nm³/h at 5.5 bar) and Venturi action to draw ready-to-use chemical solution from a nearby container and project it up to 7.6 m in 4 directions. The adjustable output sprays mist (fog) into the air to cover exposed surfaces and penetrate hard-to-reach areas.

Key Features

- Atomises and sprays chemical solutions using only compressed air
- Venturi action draws pre-diluted chemical from a nearby container
- Projects up to 7.6 m in 4 directions
- Damp fog (mist) fills the air and covers exposed surfaces with chemical, including hard-to-reach areas
- *Optional* needle valve can reduce chemical usage and output wetness
- Chemical pickup can be installed on the top or bottom
- Chemical resistant polypropylene construction ensures durability and years of outstanding performance
- See [Catalog 7](#) for hand held, permanently mounted and portable foggers
- Use the Lafferty [Fogger Planning Tool](#) to design the optimal fogging system for any facility

Includes

- Machined polypropylene fogger body
- Metering tip holder
- 10' chemical suction tube and strainer

OPTIONS

Stainless Steel Jug Racks

1 Gallon Round/Square	# 224200
1 Gallon Round/Square Locking	# 224200-L
2 ½ Gallon (8 ½" x 10 ½")	# 224210
5 Gallon Round/Square Locking (12" x 12")	# 224214
5 Gallon Round/Square (12" x 12")	# 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

To Control Solution Flow (Wetness of Fog)

Needle Valve, PVC, 1/4" FM # 660781

APPLICATIONS

- Sanitizers
- Agriculture/Horticulture
- Animal Health
- Dairy
- Food & Beverage
- Hatchery
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Odor Control
- Pharm/Bio
- Supermarkets
- And Many Other Applications!

REQUIREMENTS

Ready-to-Use Chemical Solution

Compressed Air up to 29.5 CFM / 50.1 Nm³/h at 5.5 bar
Minimum Air Supply Line 1/2"

