

60L / 16 GALLON INTERNAL TANK FOAMER

MODEL # 925916

OVERVIEW

The Internal 16 Gallon / 60.6 litre Tank Foamer is a foam applicator with an all stainless steel cart assembly for applying ready-to-use foaming chemicals. Connect compressed air to pressurize the 316L stainless steel ASME rated tank and to inject air into the solution to greatly increase volume and coverage ability. Rich, clinging foam is projected on to any surface up close or at distances up to 3.7 m. Each fill provides 15 minutes of foaming time.

KEY FEATURES

- 316L stainless steel, ASME rated tank and all stainless steel wetted components ensure durability and years of outstanding performance
- Projects a usable amount of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 3.7 m range)
- Covers up to 46.5 sq m in 2.5 minutes
- Adjustable foam consistency (wet/dry)
- Powered completely by compressed air
- No moving parts, virtually no maintenance required
- Available with a 141 litre tank (# 925937)
- Available with a low flow rate and 19 litre tank (# 925905) Available as a sprayer (# 925716)
- See all Lafferty tank foamers and sprayers in [Catalogue 4](#)

INCLUDES

- All stainless steel 2-wheel cart with non-marking tires
- Stainless steel hinged mounting enclosure
- 60L, 316L stainless steel, ASME rated pressure tank
- Stainless steel pressure relief pop-off valve
- Machined stainless steel foamer body
- 12.2 m discharge hose, stainless steel discharge ball valve, polypropylene foam wand and fan nozzle

OTHER ACCESSORY OPTIONS (SEE SIDE PANEL)

Stainless Steel Hose Racks

- Large Stainless Steel Hose Rack # 224150

Proportioning / Filling Options

- 1-Way Ball Valve Mixing Station (4 GPM) # 985100
- 1-Way Push Lever Mixing Station (4 GPM) # 981100
- High Volume Mixing Station (9.9 GPM) # 985835

Alternate Check Valves & Seals (EPDM Standard)

- Check Valve, Air, SS, 1/4" MM (Viton / Hast) # 491306
- O-Ring, Viton, Tank Lid, 5, 16 & 37 Gallon, ASME # 708513



REQUIREMENTS

- Ready-to-Use Chemical Solution
- Compressed Air: Up to 5 CFM / 8.45 Nm³/H
- Hose: 3/4" ID x 40'
- Nozzle: 50250

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Hatchery
- Industrial
- Military
- Paper Mill
- Pharma/Bio
- And Many Other Applications!