

# HV Foamer

MODEL # 916105-G



## OVERVIEW

The HV Foamer is a high volume foam applicator for projecting foaming chemicals on to any large surface. This venturi injection system uses standard city water pressure 2.4 - 8.6 bar to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. A high volume of rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle at distances up to 15 feet (7.6 m with zero degree nozzle). Gauges display incoming water and air pressure.

## KEY FEATURES

- Designed for foam cleaning large areas and equipment
- Projects a high volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for fast coverage (up to 4.6 m range)
- Covers up to 500 sq ft (46.5 sq m) in 1 minute
- Zero degree nozzle for up to 7.6 m range
- Adjustable foam consistency (wet/dry)
- Water and air pressure gauges eliminate guessing to reduce set-up time and help with troubleshooting
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- High concentrate model available for tough cleaning jobs requiring strong dilution ratios (#916115-G)
- See other configurations of Lafferty city water pressure foamers in [Catalog 1](#)

## INCLUDES

- Stainless steel mounting bracket
- Machined polypropylene foamer body
- Easy-to-read pressure gauges for incoming water and air
- 20 color-coded precision metering tips to set dilution ratios
- 15.2 M discharge hose with stainless steel discharge ball valve
- Polypropylene foam wand with fan and zero degree nozzles

## OPTIONS

<b>Stainless Steel Hose Racks</b> Large Stainless Steel Hose Rack	# 224150
<b>Stainless Steel Jug Racks</b> 2 ½ Gal. (8 ½" x 10 ½")	# 224210
5 Gallon (12" x 12") Round/Square	# 224215
<b>Safe Flow Lid™ for 1 Gallon Jugs</b> Lid, Suction Tube, and Strainer	# 709101
<b>Alternate Check Valves - EPDM Standard</b> Check Valve, Chemical, PP/Viton, 1/4"	# 491315
Check Valve, Air, SS/Viton, 1/4"	# 491306

## APPLICATIONS

- Large Vehicle Washing
- Agriculture/Horticulture
- Food & Beverage
- Industrial
- Military
- Paper Mill



## REQUIREMENTS

### Chemical Concentrate

<b>Water</b>	up to 71°C
Temperature	2.4 to 8.6 bar
Pressure	15.1 L/min @ 2.8 bar
Flow	3/4"
Supply Line	up to 5 CFM / 8.5 Nm³/h
<b>Compressed Air</b>	1" ID x 15.2 m
<b>Hose</b>	00400 or 50400
<b>Nozzle Dilution Ratio Range</b>	914:1 to 6:1 @ 2.8 bar