



SpotOn®

SPRAYER CALIBRATOR MODEL SC-2

How Do You Ensure Accurate Nozzle Flow and Minimise Liquid Wastage?



NEW!

- Automatically calculates nozzle wear in %
- Increased capacity and accuracy over previous model

FEATURES

No calculations or app download required:
Automatically calculates and displays nozzle flow rate in LPM and nozzle tip wear in %.

Fast and simple operation:
Readings in about 10 seconds per nozzle.

Quickly find worn spray nozzles:
Industry guidelines recommend nozzle replacement once flow rate exceeds that of the new tip by 10%.

Accurately measure true nozzle flow rate:
Today's high-tech spray nozzles can only be properly calibrated and confirmed with this knowledge.

Visit us at www.innoquestinc.com for complete details.

SPECIFICATIONS

Range:	0.08 - 8.52 LPM
Accuracy:	+/- 2% or 1 Digit
Resolution:	0.01 L/min
Fluid Compatibility:	Water & Water Based Solutions Only
Battery:	CR2032 Included (3 Year Battery Life)
Size:	3" (7.6 cm) Dia x 8.75" (22 cm) Tall
Weight:	0.6 lbs (272 g)

Every unit is hand calibrated and
verified with water to assure top
accuracy in the field.



YOUTUBE.COM



SEE THE DEMO VIDEO, SEARCH
SpotOn Sprayer Calibrator Model SC-2

Sprayer Calibrator Model SC-2 • Item #38790 • One year warranty • Made in USA