



THE  
**SPRAY NOZZLE**  
PEOPLE

## SPIN-ATEX MAXI

ATEX Zone 0 Certified  
Rotary Tank Cleaner



# TANK WASH

## DESIGN FEATURES

- ✓ ATEX Zone 0 certified
- ✓ Compact design
- ✓ Suitable for tanks up to 5m diameter
- ✓ Slotted spray
- ✓ Connection: DIN EN 228-G 1 1/2 as standard (weld-on and clip-on available on request)
- ✓ Operates in any direction
- ✓ Ideal for small containers such as pipes and filters
- ✓ Materials: 316 stainless steel

## SPRAY CHARACTERISTICS

- ✓ Self-cleaning
- ✓ Vigorous moving spray action
- ✓ Spray Angles: 360° (others available incl: 180° down, 270° down and 270° up)
- ✓ Flow rates: 110 – 380 l/min
- ✓ Working pressure: 1 - 15 bar
- ✓ Max working temp 90°C
- ✓ Max ambient temp 180°C



The Spin-Atex MAXI is a compact rotary tank cleaning head certified for use in ATEX Zone 0 environments. Powered by the wash liquid, it operates efficiently without external energy sources. Its dual-shaft design, supported by twin stainless steel bearings, allows for versatile mounting in any position. Suitable for use in: dryers, sprayers, pipes, small containers, filters and mixing vessels. With its short cleaning cycle, the Spin-Atex MAXI reduces liquid consumption by up to 60%, making it an efficient and cost-effective solution for industrial cleaning.

CALL NOW : +44 (0) 1273 400092

[www.spray-nozzle.co.uk](http://www.spray-nozzle.co.uk)

The Go-to People for successful spray engineering

### Spin-Atex Maxi Flow Rates

Materials: Nozzle 316 ss, bearings 316 ss as standard. Others available, incl. Hastelloy C22 with Hastelloy C276 bearings

Model	2 bar	3 bar	4 bar	5 bar	6 bar	7 bar	Scrubbing Diameter at 3 bar (mm)
Maxi 14.mm	110	134	155	165	190	193	4000
Maxi 16.mm	134	162	190	217	235	251	5000
Maxi 18mm	165	199	235	266	293	313	
Maxi 20 mm	195	240	280	315	350	380	

### Dimensions (mm)

